

# 3g 4g mobile jammer | mobile jammer abstract sculpture

[Home](#)

>

[phone jammer 4g oc](#)

>

3g 4g mobile jammer

- [2.4g wifi jammer](#)
- [2g 3g 4g gps jammer](#)
- [2g 3g 4g jammer](#)
- [3g 4g jammer diy](#)
- [3g 4g jammer uk](#)
- [4g 5g jammer](#)
- [4g data jammer](#)
- [4g internet jammer](#)
- [4g jammer](#)
- [4g jammer aliexpress](#)
- [4g jammer arduino](#)
- [4g jammer detector](#)
- [4g jammer diy](#)
- [4g jammer eu](#)
- [4g jammer india](#)
- [4g jammer price](#)
- [4g jammer review](#)
- [4g jammer uk](#)
- [4g jammers](#)
- [4g mobile jammer](#)
- [4g mobile jammer price](#)
- [4g network jammer](#)
- [4g network jammer circuit](#)
- [4g phone jammer](#)
- [4g phone jammer at kennywood](#)
- [4g phone jammer retail](#)
- [4g wifi jammer](#)
- [5g 4g 3g jammer](#)
- [5g 4g jammer](#)
- [buy 4g lte jammer](#)
- [cheap 4g jammer](#)
- [gsm 3g 4g jammer](#)
- [jammer 2g 3g 4g](#)
- [jammer 3g 4g wifi](#)
- [jammer 4g](#)
- [jammer 4g fai da te](#)

- [jammer 4g portable](#)
- [jammer 4g wifi gps](#)
- [jammer 4g wifi gps and camera](#)
- [jammer 4g wifi gps bank](#)
- [jammer 4g wifi gps camera](#)
- [jammer 4g wifi gps data](#)
- [jammer 4g wifi gps equipment](#)
- [jammer 4g wifi gps fishfinder](#)
- [jammer 4g wifi gps g2](#)
- [jammer 4g wifi gps g2n](#)
- [jammer 4g wifi gps garmin](#)
- [jammer 4g wifi gps guidance](#)
- [jammer 4g wifi gps handy-stoersender](#)
- [jammer 4g wifi gps in](#)
- [jammer 4g wifi gps installation](#)
- [jammer 4g wifi gps jammer](#)
- [jammer 4g wifi gps logger](#)
- [jammer 4g wifi gps not working](#)
- [jammer 4g wifi gps on this day](#)
- [jammer 4g wifi gps origins](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and cons](#)
- [jammer 4g wifi gps receiver](#)
- [jammer 4g wifi gps screen](#)
- [jammer 4g wifi gps server](#)
- [jammer 4g wifi gps service](#)
- [jammer 4g wifi gps smartwatches](#)
- [jammer 4g wifi gps tablet](#)
- [jammer 4g wifi gps units](#)
- [jammer 4g wifi gps update](#)
- [jammer 4g wifi gps use](#)
- [jammer 4g wifi gps user](#)
- [jammer 4g wifi gps visualizer](#)
- [jammer 4g wifi gps voice](#)
- [jammer 4g wifi gps watch](#)
- [jammer 4g wifi gps work](#)
- [jammer bloqueador 4g](#)
- [jammer for 4g](#)
- [jammer inhibidor 4g](#)
- [jammer portatile 4g](#)
- [jual jammer 4g](#)
- [jual jammer 4g lte](#)
- [lojackxm4g jammers c 32](#)
- [mini 4g jammer](#)
- [phone jammer 4g](#)
- [phone jammer 4g booster](#)
- [phone jammer 4g hotspot](#)

- [phone jammer 4g in](#)
- [phone jammer 4g internet](#)
- [phone jammer 4g manual](#)
- [phone jammer 4g mean](#)
- [phone jammer 4g oc](#)
- [phone jammer 4g ram](#)
- [phone jammer 4g router](#)
- [phone jammer 4g tablet](#)
- [phone jammer 4g tactical](#)
- [phone jammer 4g ultimate](#)
- [phone jammer 4g unlimited](#)
- [phone jammer 4g usb](#)
- [phone jammer 4g viettel](#)
- [phone jammer 4g voice](#)
- [phone jammer 4g vs](#)
- [portable 4g jammer](#)
- [wifi 4g jammer](#)

Permanent Link to Space-Time Equalization Techniques for New GNSS Signals  
2021/06/18

By Pratibha B. Anantharamu, Daniele Borio, and Gérard Lachapelle Spatial and temporal information of signals received from multiple antennas can be applied to mitigate the impact of new GPS and Galileo signals' binary-offset sub-carrier, reducing multipath and interference effects. New modernized GNSS such as GPS, Galileo, GLONASS, and Compass broadcast signals with enhanced correlation properties as compared to the first generation GPS signals. These new signals are characterized by different modulations that provide improved time resolution, resulting in more precise range measurements, along with the advantage of being more resilient to multipath and RF interference. One of these modulations is the binary-offset-carrier (BOC) modulation transmitted by Galileo and modernized GPS. Despite the benefits of BOC modulation schemes, difficulties in tracking BOC signals can arise. The autocorrelation function (ACF) of BOC signals is multi-peaked, potentially leading to false peak-lock and ambiguous tracking. Intense research activities have produced different BOC tracking schemes that address the issue of multi-peaked BOC signal tracking. Additionally, new tracking schemes including space-time processing can be adopted to further improve the performance of existing algorithms. Space-time equalization is a technique that utilizes spatial and temporal information of signals received from multiple antennas to compensate for the effects of multipath fading and co-channel interference. In the context of BOC signals, these kinds of techniques can be applied to mitigate the impact of the sub-carrier, which is responsible for a multi-peaked ACF, reducing multipath and interference effects. In temporal processing, traditional equalizers in time-domain are useful to compensate for signal distortions. But equalization becomes more challenging in the case of BOC signals, where the effect of both sub-carrier and multipath must be accounted for. On the other hand, by using spatial processing, it should be possible to extract the desired signal component from a set of received signals by electronically varying the antenna array directivity (beamforming). The combination of an antenna array and a

temporal equalizer results in better system performance. Hence the main objective of this research is to apply space-time processing techniques to BOC modulated signals received by an antenna array. The main intent is to enhance the signal quality, avoid ambiguous tracking and improve tracking performance under weak signal environments or in the presence of harsh multipath components. The focus of previous antenna-array processing using GNSS signals was on enhancing GNSS signal quality and mitigating interference and/or multipath related issues. Unambiguous tracking was not considered. Here, we develop a space-time algorithm to mitigate ambiguous tracking of BOC signals along with improved signal quality. The main objective is to obtain an equalization technique that can operate on BOC signals to provide unambiguous BPSK-like correlation function capable of altering the antenna array beam pattern to improve the signal to interference plus noise ratio. Space-time adaptive processing structure proposed for BOC signal tracking; the temporal filter provides signal with unambiguous ACF whereas the spatial filter provides enhanced performance with respect to multipath, interference, and noise. Initially, temporal equalization based on the minimum mean square error (MMSE) technique is considered to obtain unambiguous ACF on individual antenna outputs. Spatial processing is then applied on the correlator outputs based on a modified minimum variance distortionless response (MVDR) approach. As part of spatial processing, online calibration of the real antenna array is performed which also provides signal and noise information for the computation of the beamforming weights. Finally, the signal resulting from temporal and spatial equalization is fed to a common code and carrier tracking loop for further processing. The effectiveness of the proposed technique is demonstrated by simulating different antenna array structures for BOC signals. Intermediate-frequency (IF) simulations have been performed and linear/planar array structures along with different signal to interference plus noise ratios have been considered. A modified version of The University of Calgary software receiver, GSNRx, has been used to simultaneously process multi-antenna data. Further tests have been performed using real data collected from Galileo test satellites, GIOVE-A and GIOVE-B, using an array structure comprising of two to four antennas. A 4-channel front-end designed in the PLAN group, and a National Instruments (NI) signal vector analyzer equipped with three PXI-5661 front-ends (NI 2006) have been used to collect data synchronously from several antennas. The data collected from the antennas were progressively attenuated for the analysis of the proposed algorithm in weak signal environments. From the performed tests and analysis, it is observed that the proposed methodology provides unambiguous ACF. Spatial processing is able to efficiently estimate the calibration parameters and steer the antenna array beam towards the direction of arrival of the desired signal. Thus, the proposed methodology can be used for efficient space-time processing of new BOC modulated GNSS signals.

**Signal and Systems Model** The complex baseband GNSS signal vector received at the input of an antenna array can be modeled as (1) where

- $M$  is the number of antenna elements;
- $L$  is the number of satellites;
- $C$  is a  $M \times M$  calibration matrix capturing the effects of antenna gain/phase mismatch and mutual coupling;
- $s_i =$  is the complex  $M \times 1$  steering vector relative to the signal from the  $i$ th satellite.  $s_i$  captures the phase offsets between signals from different antennas;
- $n$  is the noise plus interference vector observed by the  $M$  antennas. The  $i$ th useful signal

component  $x_i(t)$  can be modeled as (2) where  $A_i$  is the received signal amplitude;  $d_i(t)$  models the navigation data bit;  $c_i(t)$  is the ranging sequence used for spreading the transmitted data;  $\tau_{0,i}$ ,  $f_{0,i}$  and  $\phi_{0,i}$  model the code delay, Doppler frequency and carrier phase introduced by the communication channel. The index  $i$  is used to denote quantities relative to the  $i$ th satellite. The ranging code  $c_i(t)$  is made up of several components including a primary spreading sequence, a secondary code and a sub-carrier. For a BPSK modulated signal, the sub-carrier is a rectangular window of duration  $T_c$ . In the case of BOC modulated signals, the sub-carrier is generated as the sign of a sinusoidal carrier. The presence of this sub-carrier produces a multi-peaked autocorrelation function making the acquisition/tracking processes ambiguous. In order to extract signal parameters such as code delay and Doppler frequency of the  $i$ th useful signal  $x_i(t)$ , the incoming signal is correlated with a locally generated replica of the incoming code and carrier. This process is referred to as correlation where the carrier of the incoming signal is at first wiped off using a local complex carrier replica. The spreading code is also wiped off using a ranging code generator. The signal obtained after carrier and code removal is integrated and dumped over  $T$  seconds to provide correlator outputs. The correlator output for the  $h$ th satellite and  $m$ th antenna can be modeled as: (3) where  $v_{m,k}$  are the coefficients of the calibration matrix,  $C$  and  $R(\Delta\tau_h)$  is the multi-peaked ACF.  $\tau_h$ ,  $f_{D,h}$  and  $\phi_h$  are the code delay, Doppler frequency and carrier phase estimated by the receiver and  $\Delta\tau_h$ ,  $\Delta f_{D,h}$  and  $\Delta\phi_h$  are the residual delay, frequency, and phase errors.  $\eta(t)$  is the residual noise term obtained from the processing of  $\eta(t)$ . Eq. (3) is the basic signal model that will be used for the development of a space-time technique suitable for unambiguous BOC tracking. When BOC signals are considered, algorithms should be developed to reduce the impact of that include receiver noise, interference and multipath components, along with the mitigation of ambiguities in  $R(\Delta\tau_h)$ . Space-time processing techniques have the potential to fulfill those requirements. Space-Time Processing A simplified representation of a typical space-time processing structure is provided in Figure 1. Each antenna element is followed by  $K$  taps with  $\delta$  denoting the time delay between successive taps forming the temporal filter. The combination of several antennas forms the spatial filter.  $w_{m,k}$  are the space-time weights with  $0 \leq k \leq K$  and  $0 \leq m \leq M$ .  $k$  is the temporal index and  $m$  is the antenna index. Figure 1. Block diagram of space-time processing. The array output after applying the space-time filter can be expressed as (4) where  $(w_{m,k})^*$  denotes complex conjugate. The spatial-only filter can be realized by setting  $K=1$  and a temporal only filter is obtained when  $M=1$ . The weights are updated depending on the signal/channel characteristics subject to user-defined constraints using different adaptive techniques. This kind of processing is often referred to as Space-Time Adaptive Processing (STAP). The success of STAP techniques has been well demonstrated in radar, airborne and mobile communication systems. This has led to the application of STAP techniques in the field of GNSS signal processing. Several STAP techniques have been developed for improving the performance of GNSS signal processing. These techniques exploit the advantages of STAP to minimize the effect of multipath and interference along with improving the overall signal quality. Space-time processing algorithms can be broadly classified into two categories: decoupled and joint space-time processing. The joint space-time approach exploits both spatial and temporal characteristics of the incoming signal in a single space-time filter while

the decoupled approach involves several temporal equalizers and a spatial beamformer that are realized in two separate stages (Figure 2). Figure 2. Representation of two different space-time processing techniques

When considering the decoupled approach for GNSS signals, temporal filters can be applied on the data from the different antennas whereas the spatial filter can be applied at two different stages, namely pre-correlation or post-correlation. In the pre-correlation stage, spatial weights are applied on the incoming signal after carrier wipe-off while in the post-correlation stage, spatial weights are applied after the Integrate & Dump (I&D) block on the correlator outputs. In pre-correlation processing, the update rate of the weight vector is in the order of MHz (same as the sampling frequency) whereas the post-correlation processing has the advantage of lower update rates in the order of kHz (I&D frequency). In the pre-correlation case, the interference and noise components prevail significantly in the spatial correlation matrix and would result in efficient interference mitigation and noise reduction. But the information on direct and reflected signals are unavailable since the GNSS signals are well below the noise level. This information can be extracted using post-correlation processing. In the context of new GNSS signals, efforts to utilize multi-antenna array to enhance signal quality along with interference and multipath mitigation have been documented using both joint and decoupled approaches where the problem of ambiguous signal tracking was not considered. In our research, we considered the decoupled space-time processing structure. Temporal processing is applied at each antenna output and spatial processing is applied at the post-correlation stage. Temporal processing based on MMSE equalization and spatial processing based on the adaptive MVDR beamformer are considered. Methodology The opening figure shows the proposed STAP architecture for BOC signal tracking. In this approach, the incoming BOC signals are at first processed using a temporal equalizer that produces a signal with a BPSK-like spectrum. The filtered spectra from several antennas are then combined using a spatial beamformer that produces maximum gain at the desired signal direction of arrival. The beamformed signal is then fed to the code and carrier lock loops for further processing. The transfer function of the temporal filter is obtained by minimizing the error: (5) where  $H(f)$  is the transfer function of the temporal filter that minimizes the MSE,  $\epsilon$ MMSES, between the desired spectrum,  $G_D(f)$ , and filtered spectrum,  $G_x(f)H(f)$ . The spectrum of the incoming BOC signal is denoted by  $G_x(f)$ .  $\lambda$  is a weighting factor determining the impact of noise with respect to that of an ambiguous correlation function.  $N_0$  is the noise power spectral density and  $C$  the carrier power. The desired spectrum is considered to be a BPSK spectrum. Since this type of processing minimizes the MSE, it is denoted MMSE Shaping (MMSES). Figure 3 shows a sample plot of the ACF obtained after applying MMSES on live Galileo BOCs(1,1) signals collected from the GIOVE-B satellite. The input C/N0 was equal to 40 dB-Hz and the ACF was averaged over 1 second of data. It can be observed that the multi-peaked ACF was successfully modified by MMSES to produce a BPSK-like ACF without secondary peaks. Also narrow ACF were obtained by modifying the filter design for improved multipath mitigation. Thus using temporal processing, the antenna array data are devoid of ambiguity due to the presence of the sub-carrier. After temporal equalization, the spatial weights are computed and updated based on the following information: The signal and noise covariance matrix obtained from the correlator outputs; Calibration parameters estimated to minimize

the effect of mutual coupling and antenna gain/phase mismatch; Satellite data decoded from the ephemeris/almanac containing information on the GNSS signal DoA. The weights are updated using the iterative approach for the MVDR beamformer to maximize the signal quality according to the following steps: Step 1: Update the estimate of the steering vector for the  $h$ th satellite using the calibration parameters as: (6) Here  $v_{i,j}$  represents the estimated calibration parameters using the correlator outputs given by Eq. (3) and  $s_{m,h}$  is the element of the steering vector computed using the satellite ephemeris/almanac data. Step 2: Update the weight vector (the temporal index,  $k$ , is removed for ease of notation) using the new estimate of the covariance matrix and steering vector as (7) where  $s$  is the input signal after carrier wipe-off. Repeat Steps 1 and 2 until the weights converge. Finally compute the correlator output to drive the code and carrier tracking loop according to Equation (4). The C/N0 gain obtained after performing calibration and beamforming on a two-antenna linear array and four-antenna planar array data collected using the four channel front-end is provided in Figure 4 and Figure 5. The C/N0 plots are characterized by three regions: Single Antenna that provides C/N0 estimates obtained using  $s_{0,h}$  alone; Before Calibration that provides C/N0 estimates obtained by compensating only the effects of the steering vector,  $s_i$ , before combining the correlator outputs from all antennas; After Calibration that provides C/N0 estimates obtained by compensating the effects of both steering vector,  $s_i$  and calibration matrix,  $C$ , before combining correlator outputs from all antennas. After calibration, beamforming provides approximately a C/N0 gain equal to the theoretical one on most of the satellites whereas before calibration, the gain is minimal and, in some cases, negative with respect to the single antenna case. These results support the effectiveness of the adopted calibration algorithm and the proposed methodology that enables efficient beamforming. Figure 4. C/N0 estimates obtained after performing calibration and beamforming on linear array data. Figure 5. C/N0 estimates obtained after performing calibration and beamforming on the planar array data. Results and Analysis IF simulated BOCs(1,1) signals for a 4-element planar array with array spacing equal to half the wavelength of the incoming signal has been considered to analyze the proposed algorithm. The input signal was characterized by a C/N0 equal to 42 dB-Hz at an angle of arrival of  $20^\circ$  elevation and  $315^\circ$  azimuth angle. A sample plot of the antenna array pattern using the spatial beamformer is shown in Figure 6. In the upper part of Figure 6, the ideal case in the absence of interference was considered. The algorithm is able to place a maximum of the array factor in correspondence of the signal DoA. Figure 6. Antenna array pattern for a 4-element planar array computed using a MVDR beamformer in the presence of two interference sources. In the bottom part, results in the presence of interference are shown. Two interference signals were introduced at 60 and 45 degree elevation angles. It can be clearly observed that, in the presence of interference, the MVDR beamformer successfully adapted the array beam pattern to place nulls in the interference DoA. In order to further test the tracking capabilities of the full system, semi-analytic simulations were performed for the analysis of digital tracking loops. The simulation scheme is shown in Figure 7 and consists of  $M$  antenna elements. Each antenna input for the  $h$ th satellite is defined by a code delay ( $\tau_{m,h}$ ) and a carrier phase value ( $\varphi_{m,h}$ ) for DLL and PLL analysis.  $\varphi_{m,h}$  captures the effect of mutual coupling, antenna phase mismatch and phase effects due to different antenna

hardware paths. To analyze the post-correlation processing structure, each antenna input is processed independently to obtain the error signal,  $\Delta\tau_{m,h} / \Delta\phi_{m,h}$  as where are the current delay/phase estimates. Figure 7. Semi-analytic simulation model for a multi-antenna system comprising M antennas with a spatial beamformer. Each error signal is then used to obtain the signal components that are added along with the independent noise components, . The combined signal and noise components from all antenna elements are fed to the spatial beamformer to produce a single output according to the algorithm described in the Methodology section. Finally, the beamformer output is passed through the loop discriminator, filter and NCO to provide a new estimate . The Error to Signal mapping block and the noise generation process accounts for the impact of temporal filtering. Figure 8 shows sample tracking jitter plots for a PLL with a single, dual and three-antenna array system obtained using the structure described above. Figure 8. Phase-tracking jitter obtained for single, dual and three-antenna linear array as a function of the input C/N0 for a Costas discriminator (20 milliseconds coherent integration and 5-Hz bandwidth). The number of simulation runs considered was 50000 with a coherent integration time of 20 ms and a PLL bandwidth equal to 5 Hz. As expected the tracking jitter improves when the number of antenna elements is increased along with improved tracking sensitivity. As expected, the C/N0 values at which loss of lock occurs for a three antenna system is reduced with respect to the single antenna system, showing its superiority. Real data analysis. Figure 9 shows the experimental setup considered for analysis of the proposed combined space-time algorithm. Two antennas spaced 8.48 centimeters apart were used to form a 2-element linear antenna array structure. The NI front-end was employed for the data collection process to synchronously collect data from the two-antenna system. Data on both channels were progressively attenuated by 1 dB every 10 seconds to simulate a weak signal environment until an attenuation of 20 dB was reached. When this level of attenuation was reached, the data were attenuated by 1 dB every 20 seconds to allow for longer processing under weak signal conditions. In this way, data on both antennas were attenuated simultaneously. Data from Antenna 1 were passed through a splitter, as shown in Figure 9, before being attenuated in order to collect signals used to produce reference code delay and carrier Doppler frequencies. Figure 9. Experimental setup with signals collected using two antennas spaced 8.48 centimeters apart. BOCs(1,1) signals collected using Figure 9 were tracked using the temporal and spatial processing technique described in the opening figure. The C/N0 results obtained using single and two antennas are provided in Figure 10. In the single antenna case, only temporal processing was used. In this case, the loop was able to track signals for an approximate C/N0 of 19 dB-Hz. Using the space-time processing, the dual antenna system was able to track for nearly 40 seconds longer than the single antenna case, thus providing around 2 dB improvement in tracking sensitivity. Figure 10. C/N0 estimates obtained using a single antenna, temporal only processing and a dual-antenna array system using space-time processing. Conclusions A combined space-time technique for the processing of new GNSS signals including a temporal filter at the output of each antenna, a calibration algorithm and a spatial beamformer has been developed. The proposed methodology has been tested with simulations and real data. It was observed that the proposed methodology was able to provide unambiguous tracking after applying the temporal filter and enhance the signal



quality after applying a spatial beamformer. The effectiveness of the proposed algorithm to provide maximum signal gain in the presence of several interference sources was shown using simulated data. C/N0 analysis for real data collected using a dual antenna array showed the effectiveness of combined space-time processing in attenuated signal environments providing a 2 dB improvement in tracking sensitivity. Pratibha B. Anantharamu received her doctoral degree from Department of Geomatics Engineering, University of Calgary, Canada. She is a senior systems engineer at Accord Software & Systems Pvt. Ltd., India. □Daniele Borio received a doctoral degree in electrical engineering from Politecnico di Torino. He is a post-doctoral fellow at the Joint Research Centre of the European Commission.□ Gérard Lachapelle holds a Canada Research Chair in Wireless Location in the Department of Geomatics Engineering, University of Calgary, where he heads the Position, Location, and Navigation (PLAN) Group.

### 3g 4g mobile jammer

Ibm 92p1105 ac adapter 19vdc 4.74a 5.5x7.9mm -(+) used 100-240va,cet technology 48a-18-1000 ac adapter 18vac 1000ma used transfor,audiovox ad-13d-3 ac adapter 24vdc 5a 8pins power supply lcd tv,axis a31207c ac adapter 12vac 500ma used 2.5x5.5 x 11.3mm 90 deg,you will learn how to make a cell phone signal jammer using 555 timer with less number of components,kodak k4500 ni-mh rapid battery charger2.4vdc 1.2a wall plug-i,2100 to 2200 mhzoutput power.a centrally located hub with a cable routed to the exterior-mounted antenna with a power supply feed.rim psm05r-068r dc adapter 6.8v dc 0.5a wall charger ite.condor d12-10-1000 ac adapter 12vdc 1a -(+)- used 2.5x5.5mm stra.a mobile jammer circuit is an rf transmitter,hon-kwang hk-u-090a060-eu european ac adapter 9v dc 0-0.6a new,delta adp-16gb a ac dc adapter 5.4vdc 3a used -(+) 1.7x4mm round,motomaster ct-1562a battery charger 6/12vdc 1.5a automatic used.raritan a10d2-06mp ac adapter 6v 1.4a power supply.raheem hagan from meadow lake is wanted for discharging a firearm with intent and reckless discharge of a fire arm.the scope of this paper is to implement data communication using existing power lines in the vicinity with the help of x10 modules,purtek bdi7220 ac adapter 9vdc 2a used -(+) 2.5x5.5x10mm 90° rou,this tool is very powerfull and support multiple vulnerabilites,hon-kwang hk-c110-a05 ac adapter 5v 0.25a i.t.e supply,12 v (via the adapter of the vehicle´s power supply)delivery with adapters for the currently most popular vehicle types (approx,aps ad-715u-2205 ac adapter 5vdc 12vdc 1.5a 5pin din 13mm used p.

mobile jammer abstract sculpture	6225
2g 3g 4g gps jammer	1665
mobile camera jammer bus	4382
2g 3g 4g jammer	5974
mobile jammer Blainville	4638
mobile jammer buy electronics	4000
4g jammer kopen	1883

mobile jammer price surge	8042
mobile jammer price insider	3333
homemade mobile jammer machine	7591
anti jammer mobile official	7086
mobile jammer history view	1908
gsm mobile jammer yellow	6909
mobile jammer pdf writer	8124
homemade mobile jammer kennywood	7826
mobile jammer Pembroke	6596
mobile jammer Daveluyville	585
anti jammer mobile arena	2503
mobile jammer price new	2187
mobile jammer report instructions	3511
pocket mobile jammer free	6540
mobile jammer online casino	6689
mobile jammer price ahca	1754
mobile phone jammer 4g	6289
mobile jammer history museum	2133
mobile jammer device locator	513

Dve dsa-6pfa-05 fus 070070 ac adapter +7vdc 0.7a used.codex yhp-1640 ac adapter 16.5vac 40va power supply plugin class,lei 411503oo3ct ac adapter 15vdc 300ma used -(+) coax cable outp.cnet ad1605c ac adapter dc 5vdc 2.6a -(+)- 1x3.4mm 100-240vac us,weather and climatic conditions,here is the project showing radar that can detect the range of an object,hppa-1121-12h ac adapter 18.5vdc 6.5a 2.5x5.5mm -(+) used 100-,lind pa1540-201 g automobile power adapter15v 4.0a used 12-16v.hon-kwang hk-u-120a015-us ac adapter 12vdc 0-0.5a used -(+)- 2x5.apd da-36j12 ac dc adapter 12v 3a power supply,panasonic ag-b6hp ac adapter 12vdc 1.8a used power supply.compaq presario ppp005l ac adapter 18.5vdc 2.7a for laptop, [5G jammers](#) .cui epa-121da-12 12v 1a ite power supply,pi ps5w-05v0025-01 ac adapter 5vdc 250ma used mini usb 5mm conne..

- [4g 3g jammer](#)
- [5g 4g 3g jammer](#)
- [4g mobile jammer](#)
- [3g 4g gsm jammer](#)
- [3g 4g signal jammer](#)
- [2g 3g 4g gps jammer](#)
- [2g 3g 4g gps jammer](#)
- [2g 3g 4g gps jammer](#)
- [2g 3g 4g gps jammer](#)
- [2g 3g 4g gps jammer](#)

- [3g 4g mobile jammer](#)
- [3g 4g jammer diy](#)
- [4g mobile jammer circuit](#)
- [4g mobile network jammer](#)
- [gps,xmradio,4g jammer walmart](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and caicos](#)
- [jammer 4g wifi gps polnt and caicos](#)



- [www.a2multimedia.pl](http://www.a2multimedia.pl)

Email:I1N0x\_z0bq@yahoo.com

2021-06-17

Artin dc 0750700 ac adapter 7.5vdc 700ma used power supply.the mobile jammer device broadcasts the signal of the same frequency to the gsm modem.li shin 0405b20220ac adapter 20vdc 11a -(+) used 5x7.4mm tip i.panasonic kx-tca1 ac adapter 9vdc 350ma +(-) 2x5.5mm used cordle,ault cs240pwrsup ac adapter 7.5vdc 260ma used 9.0vac 250ma,black and decker etpca-180021u2 ac adapter 26vdc 210ma class 2.compaq ppp003sd ac adapter 18.5v 2.7a laptop power supply..

Email:kx5\_NDle6vZ@gmx.com

2021-06-14

Cidco dv-9200 ac adapter 9vdc 200ma used -(+) 2.2x5.4mm straight.astec aa247501 ac adapter 12vdc 4.16a used -(+)- 2.5x5.5mm,this jammer jams the downlinks frequencies of the global mobile communication band- gsm900 mhz and the digital cellular band-dcs 1800mhz using noise extracted from the environment,sino-american sa120a-0530v-c ac adapter 5v 2.4a class 2 power su,.

Email:Jz\_GP6bwnK@gmx.com

2021-06-12

Sony adp-708sr ac adapter 5vdc 1500ma used ite power supply.panasonic pv-dac14d ac adapter 8.4vdc 0.65a used -(+) battery,radio shack 273-1651d u ac adapter 9vdc 500ma used with no pin i.compaq series pp2032 ac adapter 18.5vdc 4.5a 45w used 4pin femal..

Email:8Cw\_un5q@outlook.com

2021-06-11

Air rage wlb-33811-33211-50527 battery quick charger,austin adp-bk ac adapter 19v dc 1.6a used 2.5x5.5x12.6mm.mw41-1200600 ac adapter 12vdc 600ma used -(+) 2x5.5x9mm round ba.a portable mobile phone jammer fits in your pocket and is handheld,ibm 02k6808 ac adapter 16vdc 3.5a used 2.6x5.5x11mm straight.kali linux network configuration with ip address and netmask,.

Email:0pRW0\_qQGs@gmail.com

2021-06-09

Globtek gt-4076-0609 ac adapter 9vdc 0.66a -(+)- used 2.6 x 5.5.edac power ea1050b-200 ac adapter 20vdc 3a used 2.5x5.5x9mm roun,globtek gt-41052-1507 ac

adapter 7vdc 2.14a -(+) 2x5.5mm 100-240.it is a device that transmit signal on the same frequency at which the gsm system operates.we hope this list of electrical mini project ideas is more helpful for many engineering students,ac car adapter phone charger 2x5.5x9.5cm 90°right angle round ba.viewsonic api-208-98010 ac adapter 12vdc 3.6a -(+)- 1.7x4.8mm po,.